

AR Series™

Allied's Model AR 95B hydraulic impact hammer



Allied AR Series™ Hammers

Reliable Performance. Minimum Maintenance. Cost-effective Price.

The Allied Model 95B AR Series hammer is built to meet the growing demands of the rental market and to offer an alternative hydraulic hammer to contractors. The Model AR 95B hammer offers reliable performance, minimum maintenance and an attractive price which makes this hammer the perfect match for the rental industry and contractors breaking rock and demolishing concrete.

The AR 95B is a 1,600 pound hydraulic hammer that mounts easily on a 16,000 to 25,000 pound backhoe or 17,600 to 35,200 pound excavator.

The Model 95B AR Series hammer features:

- Proven design with an optimum combination of weight, power and performance
- Easy start with minimal downpressure allows operation in any position
- Steady blow energy for maximum breaking power with every blow
- Straight hydraulic hose fittings for reliable "leak-free" connections
- Tool bushings are slip-fit for easy removal reducing service time
- Supply pressure dampening for internal protection and smoother operation
- Bolt-on top-mounting bracket makes it easy to attach to excavators using quick-couplers
- High power gives excavator maximum breaking power
- Wide assortment of demolition and specialty tools to match the job



One or more of over 2,500 customized hydraulic kits from Allied provide components for mounting the Model AR 95B on backhoes and excavators. The Model AR 95B requires 18 to 33 gpm at 1,740 to 2,030 psi and it breaks at a rate of 350 to 700 blows per minute.

Demolition of concrete structures, building foundations, pavement, trench rock and over-size rock are many of the applications for the Model 95B AR Series hydraulic hammer. And, with a variety of accessories, rental customers and contractors can put the Model 95B AR Series hammer to work on the job site in more ways than ever before.

Model AR 95B Specifications

Model	AR 95B
Mounting Type	SR
Foot Pound Energy Class	1500 ft. lbs.
Operating Ranges	
Frequency Range	350-700 bpm
Hydraulic Flow Required Range	18-33 gpm (70-125 lpm)
Hydraulic Pressure Range	1,740-2,030 psi (120-140 bar)
Working Weight	1,600 lbs. (726 kg)
Overall Length	71 in. (180 cm)
Standard Demolition Tool	Cross-Cut
Tool Diameter	3.74 in. (95 mm)
Recommended Carrier Weight (Backhoe)	16,000-25,000 lbs.
Recommended Carrier Weight (Excavator)	17,600-35,200 lbs.

Mounting Type Description:

SR-Small Excavator/Backhoe Top-Mounting

For sales and service, contact your Allied Distributor:



3900 Kelley Avenue, Cleveland, Ohio 44114
Tel: 216-431-2600 Fax: 216-431-2801
e-mail: Sales@AlliedCP.com
website: <http://www.AlliedCP.com>