

BreakerLube CML™

Allied's carrier mounted lubrication system



BreakerLube CML™ — provides easy lubrication maintenance for hammers with a convenient mounting near the cab.

The Allied Construction Products, LLC BreakerLube CML (Carrier Mounted Lubrication) System is a maintenance unit for the Allied hydraulic hammers and provides semi-continuous lubrication to the hammer demolition tool and bushings. What is unique about the BreakerLube CML is that the unit is conveniently mounted near, but not in, the carrier cab.

Each time the hammer is activated, the BreakerLube CML moves chisel paste to the hammer tool holder through 60 feet of lubricant hose. When the hammer is stopped, electric power to the BreakerLube CML is turned off and the BreakerLube CML stops operating.

The Auto Shut-Off, which is standard, prevents the CML from running out of grease. When the grease level lowers to a point above the pump, the unit shuts down. The pump and the attachment will not operate until the reservoir is filled with grease.

The Allied BreakerLube CML provides the following features:

- Convenient carrier mounting near the cab
- Two sizes of large, refillable grease reservoirs
- Self-priming
- Adjustable output
- Genuine Allied Chisel Paste
- Low lubricant level will shut down hammer
- Electrically-operated (12 or 24 Vdc)
- Complete with electrical kit, hoses, connectors and mounting

The Allied BreakerLube CML provides the following benefits:

The use of Genuine Allied Chisel Paste extends the bushing and tool life of the hammers.

- Adjustable lubrication output to match hammer requirements
- Improved life of hammer wear parts
- Eliminates manual lubrication time and resulting lost production
- Fast return on investment
- Ideal for heavy-duty cycle applications and rental units
- Contributes to operator and maintenance safety

It is specially formulated with copper/graphite ingredients that distinguish it from other lubricants on the market. Genuine Allied Chisel Paste provides superior and long-lasting lubrication properties over traditional lubricants.



BreakerLube CML Specifications

Weight (reservoir empty)	12 lbs. (27 kg)
Height (with 8.5 lbs. reservoir)	16.46 in. (418 mm)
Height (with 17 lbs. reservoir)	23.71 in. (602 mm)
Width	7.42 (189 mm)
Length	12.90 in. (328 mm)
Flow Rate	Adjustable
Reservoir Capacity	8.5 lbs. (3.9 kg) 17 lbs. (7.7 kg)

Chisel Paste

Quantities	Part Number
5 Gallon Bucket	676698
15 Gallon Keg	679968

Installation Kits

Hammer Model	Kit Part Number
HR44 & HR60	572065
HR33	572064
1655, 2166 & 2577	572064
3288, 4099 & 5011	572063
7013	572067

For sales and service, contact your Allied Distributor:



3900 Kelley Avenue, Cleveland, Ohio 44114
Tel: 216-431-2600 Fax: 216-431-2601
e-mail: Sales@AlliedCP.com
website: <http://www.AlliedCP.com>