



HARDER

ın-SERIES

ITS

ł

RAMME

R

Broad operating and application range

Rammer's in Series of compact hydraulic hammers represent a giant leap forward in hydraulic hammer technology. All four models in the highly versatile range can be utilized in an infinite number of applications.

With a patented and integrated bracket that can accommodate pin or bracket mounting or quick-hitch systems, the revolutionary in hammers are able to accept a wide range of oil flows and can be mounted on virtually any mini excavator or skid steer loader, making them ideally suited to rental and multiple-carrier applications.

Easy to install

Accept wide carrier range

Easy to operate

Maintenance-free design

Featuring a massive and unbreakable trapezoidal tool that is covered by a lifetime warranty against breakage, in Series hammers are designed for a long, virtually maintenance-free service life.

Virtually maintenance-free

A revolutionary plastic

tool bushing eliminates the need for greasing while the membrane-type accumulator removes the need for recharging, lowering owning and operating costs.

Hoses are housed within the bracket for

No greasing needed

In

optimum protection from impact and abrasion. The hammers can cope with high back pressures and can with stand the rigours of even the toughest rental applications.

Unbreakable tool



in-Series hammers are typically used for:

- Equipment rental applications
- Light concrete breaking
- Light asphalt cutting
- Tunnel scaling
- Breaking brittle oversized material prior to crushing
- Breaking slag in steel casting ladles
- Frozen and hard ground breaking
- Landscaping applications

				ın22
			ın15	
		m11		
	ın8			
Mounting type	Combo	Combo	Combo	Combo
Energy class, ft. lbs.	200	250	350	500
Impact rate, bpm	400-1900	400-1900	400-1900	400-1900
Oil flow range, I/min, gal/min	12-30 3-8	14-40 4-11	16-50 4.2-13	20 - 70 5-18
Operating pressure, bar, psi	140 2030	140 2030	140 2030	150 2175
Working weight, kg, lbs	70 152	100 218	135 297	206 453
Overal length, mm, in	82 32	91 36	102 40	114 45
Standard demolition tool	Trapezoidal	Trapezoidal	Trapezoidal	Trapezoidal
Tool diameter, mm, in	104 4.1	119 4.7	131 5.2	150 5.9
Carrier weight, Ibs	1800-4000	2700-5700	3600-8000	5500-12000

For sales and service, contact your Allied Distributor:

Μ

R

A

Μ

R

E



ł

A

S

1

3900 Kelley Avenue, Cleveland, Ohio 44114 Tel: 216-431-2600 Fax: 216-431-2601 e-mail: Sales@AlliedCP.com website: http://www.AlliedCP.com

E R

D

R